



DK-A50S

DK-A50-S HAMMER

- ✓ ***SD5 SHANK DESIGN***
- ✓ ***NEW GENERATION***
- ✓ ***SUPERIOR TECHNOLOGY***
- ✓ ***STANDARD BIT DIAMETERS, 5"-5-7/8"***
- ✓ ***DELIVERS MORE ENERGY PER BLOW***
- ✓ ***HARDENED PISTON FOR EXTENDED LIFE***
- ✓ ***INNOVATIVE DESIGN FOR MAXIMUM PERFORMANCE WITH MINIMUM MAINTENANCE***

DRILL KING INTERNATIONAL


820 South Sixth Avenue ♦ Mansfield, TX 76063 ♦ USA

Main#: 817-539-2500 ♦ Fax#: 682-222-1050

Sales#: 817-539-2501 ♦ Toll Free#: 866-900-2487

sales@drillking.net ♦ www.drillking.net

The newest generation of Drill King Hammers means faster penetration, longer life, and less down time due to down hole failures.



No.	NOMENCLATURE	Qty	Part Number
HAMMER ASSEMBLY (QL50)			HADK-A50S
1	WEAR SLEEVE	1	HPDK-A5001-S
2	TOP SUB	1	HPDK-A5002
3	TOP SUB O-RING	1	HPDK-A5003
5	SPRING WASHER	1	HPDK-A5005
6	MAKE UP RING	1	HPDK-A5006
7	CHECK VALVE	1	HPDK-A5007
8	CHOKE SET	1	HPDK-A5008
9	C.V. SPRING	1	HPDK-A5009
10	AIR DISTRIBUTOR	1	HPDK-A5010
11	AIR DIS. O-RING	1	HPDK-A5011
12	CYLINDER	1	HPDK-A5012
14	PISTON	1	HPDK-A5014-S
18	BIT RET. RING	1	HPDK-A5018-S
19	BIT RET. RING O-RING	1	HPDK-A5019
20	BIT BEARING	1	HPDK-A5020-S
21	SNAP RING	2	HPDK-A5021
22	DRIVE SUB	1	HPDK-A5022-S

Drilling Parameters

Working Pressure	150-350
Application Bit	5"-5-7/8"
Feed Force (lbs.)	1000-3700

Air Consumption at Different Working Pressures

150 psi (scfm)	310
250 psi (scfm)	555
350 psi (scfm)	720

Dimensions & Weights

TOP SUB : 3.5" API PIN	
Tool Length (in)	46.7"
Outside Dia. (in)	4.76"
Stroke (in)	4.00
Weight w/o Bit (lbs)	137
Piston Weight (lbs)	25