


## DRILL KING INTERNATIONAL

820 S. Sixth Avenue • Mansfield, TX 76063 • USA Main#: 817-539-2500 • Fax#: 682-222-1050 Sales#: 817-539-2501 • Toll Free#: 866-900-2487 sales@drillking.net•www.drillking.net



## The newest generation of Drill King Hammers means faster penetration, longer life, and less down time due to down hole failures.



		Qty	Part Number
	MER ASSEMBLY 12-S)		HADK-T112-S
1	WEAR SLEEVE	1	HPDK-T14001
2	TOP SUB TOP SUB O-RING	1	HPDK-T14002 HPDK-T14003
4	WEAR WASHER	1	HPDK-T14003
6	SPRING	1	HPDK-T14004
7	CHECK VALVE	1	HPDK-T14007
8	CHOKE SET	1	HPDK-T14008
9	C.V. SPRING	1	HPDK-T14009
10	AIR DISTRIBUTOR	1	HPDK-T14010
11	AIR DIST. O-RING	1	HPDK-T14011
12	CYLINDER	1	HPDK-T14012
13	CYL RET RING	1	HPDK-T14013
14	PISTON	1	HPDK-T14014
17	PISTON RET. RING	1	HPDK-T14017
18	BIT RET. RING	1	HPDK-T14018
19	BIT RET. RING O-RING	1	HPDK-T14019
20	BEARING	1	HPDK-T14020
21	SNAP RING	1	HPDK-T14021
225	DRIVE SUB IR112S	1	HPDK-T14022S
24	WEAR WASHER BTM	11	HPDK-T14024

<b>Drilling Parameters</b>		
Working Pressure	150-250	
Application Bit	17-1/2- 22"	
Feed Force	4,500 -	
(lbs.)	8.000	

Air Consumption at Different Working Pressures		
150 psi (scfm)	880	
200 psi (scfm)	1250	
250 psi (scfm)	1700	

Dimensions & We	eights
TOP SUB : 6.58" AP	I PIN
Tool Length (in)	77
Outside Dia. (in)	10.8
SUPER CHUCK O.D (in)	14.4
Weight w/o Bit (lbs)	1565
Piston Weight (lbs)	215