

WAI-50I HAMMER

- ✓ WAI-350R SHANK DESIGN
- ✓ SUPERIOR PENETRATION RATE
- **✓ WATER-PROPELLED TECHNOLOGY**
- ✓ STANDARD BIT DIAMETERS, 5"- 6"
- **✓ EXCEPTIONAL HOLE STRAIGHTNESS**
- ✓ ENVIRONMENTALLY-FRIENDLY
- ✓ SIGNIFICANTLY REDUCED ENERGY CONSUMPTION

DRILL KING INTERNATIONAL

820 Sixth Avenue • Mansfield, TX 76063 • USA

Main#: 817-539-2500 + Fax#: 682-222-1050

Sales#: 817-539-2501 • Toll Free#: 866-900-2487


sales@drillking.net+www.drillking.net





WAI-50I

The newest generation of Drill King Water-Propelled Hammers means faster penetration, longer life, and straighter holes.



No. NOMENCLATURE	Qty Part Number
HAMMER ASSEMBLY (WAI-350)	HADK-W50.
1 TOP SUB	1 HPDK-W5002
2 FILTER CAGE	1 HPDK-W5027
3 FILTER	1 HPDK-W5026
4 VALVE CAP	1 HPDK-W5025
5 WEAR BUSHING	1 HPDK-W5024
6 VALVE	1 HPDK-W5007
7 VALVE HOUSING	1 HPDK-W5010
8 INNER TUBE	1 HPDK-W5009
9 PISTON	1 HPDK-W5014
10 CYLINDER	1 HPDK-W5012
11 PISTON BEARING	1 HPDK-W5021
12 WEAR SLEEVE	1 HPDK-W5001
13 BIT BEARING	1 HPDK-W5020
14 BIT RET.RING	1 HPDK-W5018
15 DRIVE SUB	1 HPDK-W5022
SEAL KIT	1 HPDK-
	W50SEALKIT

gpm	gpm New vs. Worn Hammer	
120 —	water consumption	
90 +		
60 +		
30		
0 +		
0	0,00,00	
	y gal/min (new)	
Flow	v gal/min (new)	
Flow	v gal/min (worn)	

Drilling Parameters		
Working Pressure	900 - 2650 (PSI)	
Application Bit	5 – 6 (in.)	
Feed Force	2750 – 5500 (lbf.)	
Rotation Speed	45 – 75 RPM	
Rotation Torque	1100 – 2240 (lbf.)	
Frequency	3300 blows/min	

Minimum - Maximum PSI	
NEW	WORN
48 - 80 gal/min	73 - 120 gal/min

Water Consumption at

Dimensions & Weights

TOP SUB: 3.5" API PIN

Weight w/o Bit (lbs.)

Tool Length (in.) 63.58

Outside Dia. (in.) 5

245

Piston Weight (lbs.) 32

COMPLETE WAI HAMMER LINE UNDER PRODUCT DEVELOPMENT WITH TARGETED MARKET LAUNCH BY THE END OF 2015

Nothing contained in this brochure is intended to extend any warranty or representation for applications expressed or implied, regarding the products described herein. Any such warranties or other terms and conditions of sale of products shall be in accordance with Drill King's standard terms and conditions of sale for such products, which are available upon request.